

HSK - Hand Welding Extruders and Bending Technology

Hand welding extruder HSK10 DE compact



BASIC EXTRUDER

- Extrusion welding from PE, PP, PVC
- temperature probe, location in the melt chamber
- rod feeding, no additional gearing
- Control units for actual / desired mass temperature
- Cold start protection
- Rod diameter 4 mm (5/32") or 3mm (1/8")
- 1 pce nozzle blank included

TECHNICAL DATA

Output	1.0 kg/h (with PE rod 4mm)
Heating extruder	300W / air 1300W
Drive	460W
Voltage	110V 50/60Hz or 230V 50Hz
Weight	3.2 kg or 7 lbs
Guarantee	screw and cylinder 24 months

DIMENSIONS

400 x 120 x 200 mm
16 x 5 x 8 in

HSK10 DE (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 1300 W

ADDITIONAL EQUIPMENT

▪ Welding nozzles	Extruder nozzle preheating	Angle adaptor
▪ Transportation box	Prolongation	Air compactor
▪ Welding rod	Widen	

Technical execution subject to modifications